

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Name of the substance	Propylene
Identification number	601-011-00-9 (Index number)
Registration number	-
Synonyms	None.
SDS number	WC001
Product code	MAP-Pro™, PRO-Max™, MAPP
Issue date	26-February-2017
Version number	01
Revision date	-
Supersedes date	-

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Hand Torch Fuel
Uses advised against	None known.

1.3. Details of the supplier of the safety data sheet

Manufacturer/Supplier	Rothenberger UK Limited
Address	2 Kingsthorpe Park, Henson Way Kettering, Northants, NN16 8PX
Contact person	Sales
E-mail address	info@rothenberger.co.uk
Telephone number	+44 (0) 1536 310 300 / Fax: +44 (0) 1536 310 600
Emergency telephone number	+44 (0) 1536 310 300 / Fax: +44 (0) 1536 310 600

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture**

The substance has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended**Physical hazards**

Flammable gases (including chemically unstable gases)	Category 1	H220 - Extremely flammable gas.
Gases under pressure	Liquefied gas	H280 - Contains gas under pressure; may explode if heated.

Hazard summary Contents under pressure. Will be easily ignited by heat, spark or flames. Heat may cause the containers to explode. May displace oxygen and cause rapid suffocation.

2.2. Label elements**Label according to Regulation (EC) No. 1272/2008 as amended****Hazard pictograms**

Signal word Danger

Hazard statements

H220	Extremely flammable gas.
H280	Contains gas under pressure; may explode if heated.

Precautionary statements**Prevention**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Response

P377 Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

P381 Eliminate all ignition sources if safe to do so.

Storage

P410 + P403 Protect from sunlight. Store in a well-ventilated place.

Disposal

Dispose of waste and residues in accordance with local authority requirements.

Supplemental label information None.

2.3. Other hazards May displace oxygen and cause rapid suffocation. Not a PBT or vPvB substance or mixture.

SECTION 3: Composition/information on ingredients

3.1. Substances

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	INDEX No.	Notes
Propylene	99.5 - 100	115-07-1 204-062-1	-	601-011-00-9	
Classification:	Flam. Gas 1;H220, Press. Gas;H280				U

Impurities

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	INDEX No.	Notes
Propane	0 - 0.5	74-98-6 200-827-9	-	601-003-00-5	

Composition comments Gas concentrations are in percent by volume.
The full text for all H-statements is displayed in section 16.

SECTION 4: First aid measures

General information If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

4.1. Description of first aid measures

Inhalation Remove from further exposure. For those providing assistance, avoid exposure to yourself or others. Use adequate respiratory protection. If respiratory tract irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance. If breathing has stopped, assist ventilation with a mechanical device or use mouth-to-mouth resuscitation.

Skin contact Not likely, due to the form of the product. If frostbite occurs, immerse affected area in warm water (not exceeding 105°F/41°C) for at least 15 minutes. Get medical attention immediately.

Eye contact Not likely, due to the form of the product. If frostbite occurs, immediately flush eyes with plenty of warm water (not exceeding 105°F/41°C) for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention promptly if symptoms persist or occur after washing.

Ingestion This material is a gas under normal atmospheric conditions and ingestion is unlikely.

4.2. Most important symptoms and effects, both acute and delayed Exposure to rapidly expanding gas or vapourizing liquid may cause frostbite ("cold burn"). Very high exposure can cause suffocation from lack of oxygen. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Asphyxiation may bring about unconsciousness without warning and so rapidly that victim may be unable to protect himself.

4.3. Indication of any immediate medical attention and special treatment needed Exposure may aggravate pre-existing respiratory disorders. Provide general supportive measures and treat symptomatically.

SECTION 5: Firefighting measures

General fire hazards Extremely flammable gas. Contents under pressure. Pressurised container may explode when exposed to heat or flame.

5.1. Extinguishing media

Suitable extinguishing media Dry chemical powder. Carbon dioxide (CO₂). Water fog. Foam.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture Extremely flammable gas. During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Special protective equipment for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Special fire fighting procedures

Do not extinguish fires unless gas flow can be stopped safely; explosive re-ignition may occur. Promptly isolate the scene by removing all persons from the vicinity of the incident. No action shall be taken involving any personal risk or without suitable training. For fires involving this material, do not enter any enclosed or confined fire space without proper protective equipment, including self-contained breathing apparatus. Stop flow of material. Use water to keep fire exposed containers cool and to protect personnel effecting shutoff. If a leak or spill has not ignited, use water spray to disperse the vapors and to protect personnel attempting to stop leak. Prevent runoff from fire control or dilution from entering streams, sewers or drinking water supply.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. Cool containers with flooding quantities of water until well after fire is out.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****For non-emergency personnel**

Evacuate the area promptly. No action shall be taken involving any personal risk or without suitable training. In the event of a leak evacuate all personnel until ventilation can restore oxygen concentrations to safe levels. Keep unnecessary personnel away. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Wear appropriate personal protective equipment (See Section 8).

For emergency responders

Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up.

6.2. Environmental precautions

Should not be released into the environment. Prevent further leakage or spillage if safe to do so.

6.3. Methods and material for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Stop leak if you can do so without risk. If possible, turn leaking containers so that gas escapes rather than liquid. Isolate area until gas has dispersed.

6.4. Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. All equipment used when handling the product must be grounded. Do not breathe gas. Avoid prolonged exposure. Do not enter storage areas or confined spaces unless adequately ventilated. Use only outdoors or in a well-ventilated area. Oxygen concentration should not fall below 19.5 % at sea level (pO₂ = 135 mmHg). Mechanical ventilation or local exhaust ventilation may be required. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Store at temperatures not exceeding 49°C/120°F. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Cylinders should be stored upright, with valve protection cap in place, and firmly secured to prevent falling or being knocked over. Protect cylinders from damage. Stored containers should be periodically checked for general condition and leakage. Store in original tightly closed container. Keep container tightly closed. Store in a well-ventilated place. Use care in handling/storage. Store away from incompatible materials (see section 10 of the SDS).

7.3. Specific end use(s)

Hand Torch Fuel.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational exposure limits**

No exposure limits noted for ingredient(s).

Biological limit values

No biological exposure limits noted for the ingredient(s).

Recommended monitoring procedures

Follow standard monitoring procedures.

Derived no effect levels (DNELs)

Not available.

Predicted no effect concentrations (PNECs)

Not available.

Control banding approach

No data available.

8.2. Exposure controls**Appropriate engineering controls**

Provide adequate ventilation and minimize the risk of inhalation of gas. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

Individual protection measures, such as personal protective equipment**General information**

Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.

Eye/face protection	Wear approved safety glasses or goggles.
Skin protection	
- Hand protection	Wear appropriate chemical resistant gloves. Nitrile, butyl rubber or neoprene gloves are recommended.
- Other	Wear protective clothing appropriate for the risk of exposure.
Respiratory protection	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Wear air supplied respiratory protection.
Thermal hazards	Contact with liquefied gas might cause frostbites, in some cases with tissue damage. Wear appropriate thermal protective clothing, when necessary.
Hygiene measures	Do not eat, drink or smoke when using the product. Wash thoroughly after handling. Provide eyewash station and safety shower. Handle in accordance with good industrial hygiene and safety practices.
Environmental exposure controls	Environmental manager must be informed of all major releases.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state	Gas.
Form	Compressed liquefied gas.
Colour	Colourless.
Odour	Hydrocarbon or mercaptan if odorized.
Odour threshold	Not available.
pH	Not applicable.
Melting point/freezing point	-185 °C (-301 °F)
Initial boiling point and boiling range	-48 °C (-54.4 °F)
Boiling point pressure	101.33 kPa
Flash point	-107.8 °C (-162.0 °F)
Evaporation rate	Not applicable.
Flammability (solid, gas)	Extremely flammable gas.

Upper/lower flammability or explosive limits

Flammability limit - lower (%)	2 % v/v
Flammability limit - upper (%)	11 % v/v
Vapour pressure	109.73 PSIG
Vapor pressure temp.	21 °C (69.8 °F)
Vapour density	1.5 (Air=1)
Vapor density temp.	0 °C (32 °F) (gas)
Relative density	0.52 (liquid) (H ₂ O=1)
Solubility(ies)	384 mg/l - Slightly soluble in water.
Partition coefficient (n-octanol/water)	1.77
Auto-ignition temperature	497.22 °C (927 °F)
Decomposition temperature	Not available.
Viscosity	Not available.
Explosive properties	Not explosive.
Oxidising properties	Not oxidising.

9.2. Other information

Molecular weight	42 g/mol
Percent volatile	100 %
Surface tension	16.7 mN/m (90 °C (194 °F))

SECTION 10: Stability and reactivity

10.1. Reactivity	Incompatible materials.
-------------------------	-------------------------

10.2. Chemical stability	Stable under normal temperature conditions and recommended use.
10.3. Possibility of hazardous reactions	Polymerization will not occur. May form explosive mixture with air. This product may react with oxidizing agents.
10.4. Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
10.5. Incompatible materials	Strong oxidising agents. Strong acids. Halogens.
10.6. Hazardous decomposition products	Thermal decomposition of this product can generate carbon monoxide and carbon dioxide. Hydrocarbons.

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation	High concentrations: Suffocation (asphyxiant) hazard - if allowed to accumulate to concentrations that reduce oxygen below safe breathing levels. Breathing of high concentrations may cause dizziness, light-headedness, headache, nausea and loss of co-ordination. Continued inhalation may result in unconsciousness.
Skin contact	Contact with liquefied gas may cause frostbite.
Eye contact	Contact with liquefied gas may cause frostbite.
Ingestion	This material is a gas under normal atmospheric conditions and ingestion is unlikely.

Symptoms Exposure to rapidly expanding gas or vapourizing liquid may cause frostbite ("cold burn"). Very high exposure can cause suffocation from lack of oxygen. Victim may not be aware of asphyxiation. Asphyxiation may bring about unconsciousness without warning and so rapidly that victim may be unable to protect themselves.

11.1. Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.

Components	Species	Test results
Propylene (CAS 115-07-1)		
Acute		
Inhalation		
Gas		
LC50	Rat	> 65000 ppm, 4 Hours
Skin corrosion/irritation	Based on available data, the classification criteria are not met.	
Serious eye damage/eye irritation	Based on available data, the classification criteria are not met.	
Respiratory sensitisation	Based on available data, the classification criteria are not met.	
Skin sensitisation	Based on available data, the classification criteria are not met.	
Germ cell mutagenicity	Based on available data, the classification criteria are not met.	
Carcinogenicity	Based on available data, the classification criteria are not met.	

IARC Monographs. Overall Evaluation of Carcinogenicity

Propylene (CAS 115-07-1) 3 Not classifiable as to carcinogenicity to humans.

Reproductive toxicity	Based on available data, the classification criteria are not met.
Specific target organ toxicity - single exposure	Based on available data, the classification criteria are not met.
Specific target organ toxicity - repeated exposure	Based on available data, the classification criteria are not met.
Aspiration hazard	Not likely, due to the form of the product.
Mixture versus substance information	No information available.
Other information	Exposure over a long period of time may cause central nervous system effects.

SECTION 12: Ecological information

12.1. Toxicity	The product is not expected to be hazardous to the environment.
12.2. Persistence and degradability	The product is readily biodegradable.
12.3. Bioaccumulative potential	The product is not expected to bioaccumulate.

Partition coefficient

n-octanol/water (log Kow)

Propylene (CAS 115-07-1)	1.77
Propane (CAS 74-98-6)	2.36

Bioconcentration factor (BCF)	Not available.
12.4. Mobility in soil	Not relevant, due to the form of the product.
12.5. Results of PBT and vPvB assessment	Not a PBT or vPvB substance or mixture.
12.6. Other adverse effects	The product contains volatile organic compounds which have a photochemical ozone creation potential.
12.7. Additional information	None.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste	Dispose in accordance with all applicable regulations.
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal.
EU waste code	16 05 04* The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Disposal methods/information	Use the container until empty. Do not dispose of any non-empty container. Empty containers have residual vapor that is flammable and explosive. Cylinders should be emptied and returned to a hazardous waste collection point. Do not puncture or incinerate even when empty. Dispose in accordance with all applicable regulations.
Special precautions	Dispose of in accordance with local regulations.

SECTION 14: Transport information

ADR

14.1. UN number	UN1077
14.2. UN proper shipping name	Propylene
14.3. Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Hazard No. (ADR)	23
Tunnel restriction code	B/D
14.4. Packing group	-
14.5. Environmental hazards	No
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

RID

14.1. UN number	UN1077
14.2. UN proper shipping name	Propylene
14.3. Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1 (+13)
14.4. Packing group	-
14.5. Environmental hazards	No
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

ADN

14.1. UN number	UN1077
14.2. UN proper shipping name	Propylene
14.3. Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
14.4. Packing group	-
14.5. Environmental hazards	No
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

IATA

14.1. UN number	UN1077
------------------------	--------

14.2. UN proper shipping name	Propylene
14.3. Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
14.4. Packing group	-
14.5. Environmental hazards	No
ERG Code	10L
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

IMDG

14.1. UN number	UN1077
14.2. UN proper shipping name	PROPYLENE
14.3. Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
14.4. Packing group	-
14.5. Environmental hazards	
Marine pollutant	No
EmS	F-D, S-U
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code Not established.

General information

Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers: Ensure that containers are firmly secured. Ensure cylinder valve is closed and not leaking. Ensure valve outlet cap nut or plug (where provided) is correctly fitted. Ensure valve protection device (where provided) is correctly fitted. Ensure adequate ventilation. Ensure compliance with applicable regulations.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Not listed.

Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended

Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA

Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorisation, as amended

Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

Propylene (CAS 115-07-1)

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Not listed.

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

Propane (CAS 74-98-6)

Propylene (CAS 115-07-1)

Other regulations

The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended.

National regulations

Follow national regulation for work with chemical agents. Young people under 18 years old are not allowed to work with this product according to EU Directive 94/33/EC on the protection of young people at work, as amended.

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations

PBT: Persistent, bioaccumulative and toxic.
vPvB: Very Persistent and very Bioaccumulative.
DNEL: Derived No-Effect Level.
PNEC: Predicted No-Effect Concentration.
STEL: Short term exposure limit.
TWA: Time weighted average.
PEL: Permissible Exposure Limit.
LC50: Lethal Concentration, 50%.

References

HSDB® - Hazardous Substances Data Bank
IARC Monographs. Overall Evaluation of Carcinogenicity
National Toxicology Program (NTP) Report on Carcinogens
ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices
EPA: AQUIRE database
NLM: Hazardous Substances Data Base

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

Full text of any H-statements not written out in full under Sections 2 to 15

H220 Extremely flammable gas.
H280 Contains gas under pressure; may explode if heated.

Training information

Follow training instructions when handling this material.

Disclaimer

All information in this Safety Data Sheet is believed to be accurate and reliable. However, no guarantee or warranty of any kind is made with regard to the accuracy of information or the suitability of the recommendations contained herein. It is the user's responsibility to assess the safety and toxicity of this product under their own conditions of use and to comply with all applicable laws and regulations.